

**GLOBATT™**  
THE DRIVE WITHIN

**CALCIUM+**  
MAINTENANCE FREE BATTERY

HIGH CRANKING PERFORMANCE  
DURABLE & ROBUST DESIGN  
ECO FRIENDLY

**56618** PACE  
**115D31R** ACE  
**115E41R/L** CALCIUM+

MANUFACTURED BY ISO 9001:2008 & ISO 14001:2004 CERTIFIED COMPANY

**www.globatt-battery.com**

**GERMAN TECHNOLOGY**

## TECHNICAL SPECIFICATION

Battery Type Group No.	New JIS	AH @ 20	Dimension (mm)			Cell Layout	Terminal Type	CCA (0°C)	Filled Weight (kg)
			L	W	H				
<b>Passenger Car Range</b>									
B20	50B20R/L	42	197	129	225	1/2	B	420	11.4
	60B24R/L	52	238	129	225	1/2	B	530	13.6
B24	60B24R(S)/LS	52	238	129	225	1/2	A	530	13.6
	90D23R/L	70	231	173	225	1/2	A	600	16.8
D26	70D26R/L	62	259	173	225	1/2	A	550	17.3
	105D26R/L	78	259	173	225	1/2	A	700	19.1
D31	105D31R/L	82	306	173	225	1/2	A	720	21.8
	115D31R/L	92	306	173	225	1/2	A	800	22.8
<b>Commercial Vehical Range</b>									
E41	115E41R/L	100	409	173	233	1/2	A	830	27.6
F51	135F51R/L	120	510	182	248	3/4	A	1100	35.0
G51	165G51R/L	150	510	221	246	3/4	A	1200	41.3
H52	210H52R/L	200	518	274	246	3/4	A	1400	54.0

HOLD DOWN AVAILABLE FOR FULL RANGE PASSENGER CAR BATTERY

Battery Type	Capacity 20HR	Dimension (mm)			Cell Layout	Terminal	CCA (0°C)	Hold Down	Filled Weight (kg)
		L	W	H					
<b>DIN Range</b>									
54434	44	207	175	190	2	1	420	B13	12.20
56218	62	242	175	190	1	1	620	B13	16.00
56219	62	242	175	190	2	1	620	B13	16.00
57439	74	278	175	175	2	1	680	B13	17.60
57512	75	278	175	190	2	1	780	B13	18.30
58035	80	315	175	190	2	1	870	B13	21.00
58514	85	315	175	175	2	1	840	B13	19.90
59018	92	353	175	190	2	1	900	B13	23.00
60044	100	353	175	190	2	1	1000	B13	24.00

LOW HEIGHT (175 mm) AVAILABLE FOR ALL DIN TYPES

**Energy Systems Transnational Pte Ltd**  
69C Tuas South Ave 1  
Singapore 637500  
Tel : 62626286  
Fax: 62626936  
Email: [sales@estpower.net](mailto:sales@estpower.net)  
Website: [www.est-group.net](http://www.est-group.net)

